



Daylight sensor




Daylight sensor for IL2 PLUS tracks. The sensor measures the brightness of the workspace and adjusts the emitted light intensity. The nominal value is adjustable. Increasing daylight decreases the amount of artificial light.

- Easy to mount in IL2 PLUS tracks
- Direct contacting to the 1 – 10 V interface
- Nominal value setting through potentiometer
- Energy saving

| ELECTRONICS | |
|-------------------------------------|--|
| Sensor type | Daylight sensor |
| Interface | 1 – 10 V |
| Protection class | Class II |
| Connection | Plug contact for IL2 PLUS supporting rails |
| Number of controllable light points | Max. 80 driver |

| INSTALLATION DATA | |
|--------------------------|-------------------------------------|
| Max. installation height | 8 m |
| Sensor registration area | cone shaped, approx. 90° beam angle |
| Sensor operation range | 20 – 800 lx |
| Nominal value setting | through potentiometer |

| ADDITIONAL DATA | |
|---------------------------|-------------------------|
| Dimensions (L x W x H) | 175 x 80 x 75 mm |
| Weight | 185 g |
| Sensor | Makrolon / Polycarbonat |
| Housing | PPT40 |
| Ambient temperature range | 0 – 40°C |
| IP Certification | IP 20 |

| | |
|---------------|---|
| Certification |    |
|---------------|---|

Issue 03 / 2014